

1           UNIFORM SEAT COVER AND SEAT FASHIONED WITH SAME

2

3

4                           Field of the Invention

5

6           This invention relates to uniforms and to seats and to  
7 seat covers and, more particularly, to a uniform seat cover  
8 and to seats fashioned with uniform seat covers.

9

10                           Background of the Invention

11

12           A uniform is an identifying outfit or style of dress  
13 worn by the members of a given group, whether a team, a  
14 profession, an organization, an establishment, etc.  
15 Uniforms are important because give others the ability to  
16 distinguish between the members of different groups.  
17 Exemplary of the many types of uniforms are those worn by  
18 members of amateur and professional sport teams such as  
19 basketball, football, baseball, soccer, hockey and softball  
20 teams, and those worn by members of military organizations  
21 such as the United States Army, Navy, Air Force and Marines,  
22 etc.

23

24           People are usually very proud of their memberships,  
25 whether past or present, and many organizations, especially

1 sports organizations, enjoy a following of ardent  
2 enthusiasts. For sports fans and other fans and for those  
3 of proud membership, uniforms are highly valued and  
4 essentially memorialize an appreciation of membership and  
5 fans' admiration of certain groups, professions and  
6 organizations.

7  
8 In response to this, it would be highly desirable to  
9 provide a way of exploiting uniform dress in combination  
10 with seats and especially vehicle seats and further in  
11 combination with spectator seats of a stadium or arena that  
12 is decorated with team adornment of a sports team  
13 organization.

## Summary of the Invention

The above problems and others are at least partially solved and the above purposes and others realized in new and improved apparatus that includes a seat having an attached uniform. The seat includes a seat portion and an attached seat back portion. The uniform includes a uniform top and a uniform bottom. The uniform top is fitted over the seat back portion and the uniform bottom is fitted over the seat portion. The uniform top and the uniform bottom support uniform adornment that identifies a member of a given group. The seat back portion includes a lower end attached to the seat portion and an opposing upper end, and the uniform top includes a collared neck opening situated at the upper end of the seat back portion. The uniform top includes one of  
a) sleeves located on either side of the neck opening and  
b) arm openings located on either side of the neck opening. Further the uniform top and the uniform bottom support straps that secure the uniform top and the uniform bottom to the seat and to each other. An engagement assembly is carried by one of the uniform top and the uniform bottom and a detachably engaged complementary engagement assembly is carried by the other of the uniform top and the uniform bottom. Preferably, the engagement assembly is supported at an end of the one of the uniform top and the uniform bottom

1 and the complemental engagement assembly is supported at a  
2 confronting end of the other of the uniform top and the  
3 uniform bottom.

4

5 In accordance with the principle of the invention,  
6 further is a stadium for team sports events with seats for  
7 spectators and team adornment of a team decorating the  
8 stadium. Each of the seats includes a seat portion and an  
9 attached seat back portion and is furnished with an attached  
10 uniform that includes a uniform top fitted over the seat  
11 back portion and a uniform bottom fitted over the seat  
12 portion. The uniform top and the uniform bottom of each of  
13 the uniforms supports uniform adornment that identifies  
14 members of the team, as with the team adornment adorning the  
15 stadium.

16

17 Consistent with the foregoing, the invention also  
18 contemplates associated methods.

BRIEF DESCRIPTION OF THE DRAWINGS

Referring to the drawings:

FIG. 1 is a perspective view of a uniform attached to a seat, in accordance with the principle of the invention, the uniform including a uniform top fitted over a seat back portion of the seat and a uniform bottom fitted over a seat portion of the seat;

FIG. 2 is a side elevation of the embodiment depicted in FIG. 1;

FIG. 3 is a rear elevation of the uniform of FIG. 1;

FIG. 4 is an enlarged fragmented perspective view of the uniform of FIG. 1 illustrating an attachment assembly;

FIG. 5 is an enlarged fragmented perspective view of the uniform of FIG. 1 illustrating the uniform top detached from the uniform bottom, an engagement assembly carried by the uniform top and a detachably engagable complementary engagement assembly carried by the uniform bottom;

1        FIG. 6 is an enlarged fragmented perspective view of a  
2 zipper assembly that is capable of being employed for  
3 detachably securing a uniform top to a uniform bottom of a  
4 uniform constructed and arranged in accordance with the  
5 principle of the invention;

6

7        FIG. 7 is a bottom plan of the uniform of FIG. 1, with  
8 the uniform top shown attached to the uniform bottom;

9

10       FIG. 8 is a fragmented perspective view of a uniform  
11 attached to a seat, in accordance with the principle of the  
12 invention, an engagement element carried by the uniform and  
13 a detachably engagable complementary engagement element  
14 exploded from the seat;

15

16       FIG. 9 is a perspective view of a pair of seats each  
17 having an attached uniform, in accordance with the principle  
18 of the invention;

19

20       FIG. 10 is a representation of a stadium for team  
21 sports events with seats for spectators and team adornment  
22 of a team decorating the stadium and uniforms attached to  
23 the seats, in accordance with the principle of the  
24 invention;

1        FIG. 11 is a perspective view of a uniform attached to  
2 a seat, in accordance with an alternate embodiment of the  
3 invention, the uniform including a uniform top fitted over a  
4 seat back portion of the seat and a uniform bottom fitted  
5 over a seat portion of the seat;

6

7        FIG. 12 is a side elevation of the embodiment depicted  
8 in FIG. 11; and

9

10       FIG. 13 is a perspective view of a uniform attached to  
11 a bench, in accordance with yet another embodiment of the  
12 invention, the uniform including a uniform top fitted over a  
13 seat back portion of the bench and a uniform bottom fitted  
14 over a seat portion of the bench.

1                    DETAILED DESCRIPTION OF PREFERRED EMBODIMENTS

2

3            Turning now to the drawings, in which like reference  
4 characters indicate corresponding elements throughout the  
5 several views, attention is first directed to FIG. 1 in  
6 which is seen a uniform, embodying the principle of the  
7 instant invention, generally indicated by the reference  
8 character 20 and including a uniform top 21 fitted over a  
9 seat back portion 32 of a seat 30 and a uniform bottom 22  
10 fitted over a seat portion 31 of seat 30. FIG. 2 is  
11 exemplary of a side elevation of the embodiment depicted in  
12 FIG. 1, with the opposite side elevation being a mirror  
13 image. Seat back portion 32 includes a lower end 33  
14 attached to a rear end 35 of seat portion 31 and an opposing  
15 upper end 34, and together they are capable of supporting a  
16 person in a sitting position. Seat portion 31 includes a  
17 forward end 36 that opposes its rear end 35. Seat 30 is  
18 generally representative of a vehicular seat such as a car  
19 seat and the like and is designed to be attached inside the  
20 passenger compartment of a vehicle. The invention can be  
21 employed with any seat of a type including a seat portion  
22 having an attached seat back portion. It is instructive of  
23 the invention that when uniform 20 is attached to seat 30,  
24 seat back portion 32 and seat portion 31 look like the torso  
25 and upper legs from waist to knees of a uniformed member of



1 a group. Top 21 is sized and shaped to be capable of being  
2 fitted over seat back portion 32 and bottom 22 is sized and  
3 shaped to be capable of being fitted over seat portion 31.  
4 Seat 30 can be of any size and top 21 and bottom 22 are  
5 sized appropriately so that they can be installed in  
6 accordance with the teachings herein. Seat 30 is  
7 representative of seat that is capable of accommodating a  
8 single person in a seated position, and yet seat 30 can be  
9 an elongated bench that is capable of supporting a plurality  
10 of individuals in seated positions, one beside the other.  
11 If a uniform constructed and arranged in accordance with the  
12 invention is provided in connection with an elongated seat,  
13 namely, a bench, it can be furnished to represent a  
14 plurality of uniforms side-by-side if desired and the  
15 uniforms in this embodiment can be the same or different.

16

17 Preferably, top 21 and bottom 22 are constructed of  
18 cloth material, whether natural or synthetic and whether  
19 woven or unwoven and any desired combination of natural  
20 and/or synthetic materials can be used in addition to other  
21 pliant materials. Each can be furnished with padding or  
22 padded features if desired and are assembled from various  
23 parts with sewing and/or gluing and each can be fashioned  
24 integrally as well. In accordance with the invention,  
25 uniform 20 can be fashioned from a pre-existing uniform, an

1 authentic uniform, or made so as to be a replica of a  
2 uniform.

3

4 Top 21 and bottom 22 together represent a uniform or in  
5 other words an identifying outfit or style of dress worn by  
6 the members of a given group, whether a team, a profession,  
7 an organization, an establishment, etc. Exemplary of the  
8 many types of uniforms are those worn by members of amateur  
9 and professional sport teams such as basketball, football,  
10 baseball, soccer, hockey and softball teams, and those worn  
11 by members of military organizations such as the United  
12 States Army, Navy, Air Force and Marines, and various sub-  
13 groups and organizations thereof, etc. Examples of other  
14 uniforms are those worn by chefs, the members of foreign  
15 military organizations, the members of past military  
16 organizations, etc. Still other groups, professions and  
17 organizations exist in which their members wear uniforms and  
18 this invention contemplates the top 21 and bottom 22 can be  
19 fashioned, styled and configured to represent any such  
20 uniform including any associated adornments, clothing  
21 styles, ornamentation and indicia, pockets, plackets, long  
22 sleeves, short sleeves, no sleeves, etc.

23

24 In the embodiment depicted in FIG. 1, top 21 and bottom  
25 22 represent the identifying outfit or style of dress worn

1 by the members of a football team, with top 21 representing  
2 the football jersey of the uniform and bottom 22  
3 representing the football pants of the uniform. And so top  
4 21 includes a body 40 having a front side 41 and a back side  
5 42 (FIG. 4). Body 40 further includes an open lower end 43  
6 and a shouldered upper end 44. A collar 45 is formed at  
7 upper end 44, which defines a neck opening 46 and sleeves  
8 47,48 are disposed along either side of neck opening 46 at  
9 upper end 44. Sleeves 47,48 are representative of short  
10 sleeves. Further to FIGS. 1 and 3, bottom 22 is  
11 characterized by a substantially U-shaped sidewall 50 that  
12 depends from major panel 50. Bottom 22 includes a forward  
13 end 52, which is essentially closed by sidewall 50, and a  
14 rearward end 53, which is essentially open. Sleeves 47,48  
15 can be replaced simply with arm openings as with a  
16 sleeveless jersey.

17

18 Top 21 and bottom 22 together support uniform adornment  
19 that is characterized by not only the style of top 21 but  
20 also uniform indicia 60 carried by top 21 and bottom 22,  
21 which adornment identifies or otherwise represents the  
22 identifying outfit of style of dress worn by, in accordance  
23 with the instant embodiment, members of a football team.  
24 Uniform indicia 60 include jersey indicia supported by top  
25 21 and pants indicia supported by bottom 22. If desired,

1 pants indicia and any associated pants adornments can be  
2 supported by top 21 including, for instance, waistband  
3 adornment, etc. It is instructive of the principle of the  
4 invention that football uniforms are emblazoned with jersey  
5 indicia that ornament the jersey and pants indicia that  
6 ornament the pants and the combination of the two identify  
7 the members of that specific football team and this is  
8 precisely what constitutes the jersey and pants indicia,  
9 namely, indicia 60. And so indicia 60 include numbers  
10 located at front and back sides 41,42 and at sleeves 47,48  
11 of top 21 and along the sides of bottom 22. The jersey and  
12 pants indicia, which together constitute indicia 60, are  
13 also intended to include coloring, team logos and other team  
14 identifying indicia in addition perhaps to the name of a  
15 given player, and indicia 60 are imprinted or otherwise  
16 applied to the external surfaces of top 21 and bottom 22.  
17 Indicia 60 are that of any sports team. Preferably, top 21  
18 and bottom 22 are fashioned with indications 61 that further  
19 help represent collar 45 and sleeves 47,48 in connection  
20 with top 21 and pant legs in connection with bottom 22 as  
21 generally illustrated in FIGS. 1 and 2. Preferably,  
22 indications 61 include stitched features. Indications 61  
23 can also be applied indicia, applied ribbing or other form  
24 of attached feature, etc.

1           Further to FIG. 1, it is instructive of the invention  
2   that top 21 fits over seat back portion 32 of seat 30,  
3   bottom 22 fits over seat portion 31 of seat 30, and that top  
4   21 attaches to bottom 22. Properly fitted to a seat, lower  
5   end 43 of top 21 at front face 41 meets rearward end 53 of  
6   bottom 22 at portion 51 and these described edges of top 21  
7   and bottom 22 detachably secure each other and this is  
8   discussed in greater detail, *infra*. Top 21 and bottom 22  
9   are sized and shaped adequately so as to fit well over the  
10   seat back and seat portions 32,31, respectively. Sleeves  
11   47,48 are located at upper end 44 of seat back portion 32 at  
12   either side thereof and neck opening 46 is positioned  
13   centrally over upper end 44. Preferably, top 21 and bottom  
14   22 overly and protect the majority of the external surfaces  
15   of seat 30 so as to protect seat 30 from wear and tear and  
16   from exposure to sunlight and from becoming stained, etc.

17

18           It is preferable to secure top 21 and bottom 22 to seat  
19   30 and for this top 21 and bottom 22 are fashioned with  
20   attached straps 70,71, respectively, as seen best in FIGS. 3  
21   and 7. Straps 70,71 are attached with stitching and gluing  
22   and other ways of providing attachment can be used as well.  
23   Straps 70 are attached to lower end 43 of top 21 at back  
24   side 42, and straps 71 are attached along the lower edge of  
25   sidewall 50. Straps 70,71 can be attached at other

1 locations and any desired number of each can be employed in  
2 accordance with specific needs, and they can be made to be  
3 adjustable, elastic, etc. A variety of straps 71 are  
4 employed, including opposing pairs of straps 71 at the sides  
5 of bottom 22 that are capable of being passed along the  
6 bottom of a seat portion, the ends of which are engagable to  
7 one another so as to secure bottom 22 to the seat portion.  
8 Other ones of straps 71 at forward end 52 of bottom 22 are  
9 capable of being passed along the bottom of a seat portion,  
10 the ends of which are engagable to ends of straps 70 so as  
11 to secure bottom 22 to top 21 and further bottom 22 and top  
12 21 to a seat. The ends of straps 70,71 are furnished with  
13 attachment pairs for facilitating their mutual engagement  
14 such as engagable clasps, hook and loop fastening structure,  
15 mutual snaps and the like. As a matter of example, FIG. 4  
16 illustrates an end of one of straps 70 supporting a hook  
17 medium 80 and an engagable end of one of straps 71 furnished  
18 with a loop medium 81, and this can be reversed. Further as  
19 a matter of example in FIG. 5, shown is an end of one of  
20 straps 71 furnished with an attached hook 82 and an  
21 engagable end of an opposing one of straps 71 furnished with  
22 an attached ring 83, and this can be reversed. Hook 82 is  
23 engagable to ring 83 and this combination is exemplary of a  
24 clasp assembly and other clasp forms can be employed.

1       To provide attachment of uniform 20 to a seat, the  
2 invention also contemplates the desirability of providing a  
3 seat and seat cover 20 with mutual attachment pairs and  
4 exemplary of this teaching is the illustration of FIG. 8,  
5 which shows an attachment element 85 for attachment to a  
6 seat and a detachably engagable complemental attachment  
7 element 86 carried by seat cover 20, whether by top 21 or  
8 bottom 22. In FIG. 8, attachment element 85 is a loop  
9 medium 85A that attaches to the seat with an adhesive  
10 backing and complemental attachment element 86 is a hook  
11 medium 86A carried by an attached strap 87. Attachment  
12 element 85 can be attached to a seat in other ways and  
13 mutual snap or other suitable form of fastening structure  
14 can be employed between seat cover 20 and a seat. Those  
15 having regard for the art will appreciate that any suitable  
16 number of engagement pairs can be used to secure a uniform  
17 of the invention to a seat in accordance with the instant  
18 teachings and that engagement pairs are reversible.

19  
20       Regarding FIG. 5, a flap 90 is attached to lower end 43  
21 of top 21 at front side 41 and a flap 91 is attached to  
22 rearward end 53 of bottom 22 at portion 51. Flap 90 is an  
23 extension of front side 41 and extends along substantially  
24 the entire width of front side 41. Flap 91 is an extension  
25 of portion 51 and extends along substantially the entire

1 width of portion 51. Flap 90 supports an engagement  
2 assembly 92 and flap 91 supports a detachably engagable  
3 complementary engagement assembly 93, which secure to one  
4 another in a preferred installation of uniform 20 to a seat  
5 as previously described. In the embodiment depicted in FIG.  
6 5, assembly 92 includes a plurality of female elements 94  
7 attached toward one end of flap 90 and a loop medium 95  
8 attached toward the other side of flap 90, and assembly 93  
9 includes a plurality of male elements 96 attached to toward  
10 one end of flap 91 and a hook medium 97 attached toward the  
11 other end of flap 91. Female elements 94 are capable of  
12 receiving and coupling male elements 96 and loop medium 95  
13 is capable of engaging and securing hook medium 97. The  
14 combination of female and male elements 94,96 is exemplary  
15 of a mutual snap fastening structure and other forms can be  
16 used. The position of female and male elements 94,96 is  
17 reversible, as is the case with loop medium 95 and hook  
18 medium 97. Although snap fastening structure is used in the  
19 instant embodiment in combination with the hook and loop  
20 fastening structure, one or the other can be employed.  
21 Other fastening structure can be used for attaching the edge  
22 of lower end 43 of top 21 at front side 41 to the  
23 confronting edge of rearward end 53 of bottom 22 at portion  
24 51 and exemplary of this teaching is the attached zipper  
25 assembly 99 depicted in FIG. 6.



1       As mentioned previously, uniform 20 can be configured  
2   to resemble the uniform worn by the members of any group,  
3   profession or organization and exemplary of this teaching is  
4   the illustration set forth in FIG. 9, which depicts a pair  
5   of uniforms 100,101 that are each common to uniform 20 and  
6   include substantially the same elements, with the exception  
7   that each resembles a baseball uniform. Uniform 100 is  
8   shown as it would appear partially installed upon one car  
9   seat 102 and uniform 101 is shown as it would appear  
10   installed upon another car seat 103. In the embodiment of  
11   FIG. 9, car seats 102,103 are situated on either side of a  
12   console 104 and this combination is representative of the  
13   driver and passenger seats of many types of passenger  
14   vehicles.

15

16       Another exemplary embodiment of the invention is  
17   depicted in FIG. 10, in which is seen a representation of a  
18   stadium 120 for team sports events with seats 121 for  
19   spectators and team adornment or indicia 122 of a team  
20   decorating surfaces of stadium 120. Seats 121 are each  
21   common to seat 30 in that they each include a seat portion  
22   and an attached seat back portion. Seats 121 are situated  
23   in a row 123 and it is envisioned that stadium 120 will have  
24   a large number of rows of seats for accommodating large  
25   numbers of spectators. In FIG. 10, stadium 120 is a

1 baseball stadium and adornment or indicia 122 represent a  
2 baseball team and are applied by painting, imprinting, with  
3 attached banners and/or decals, etc.

4  
5 In accordance with the principle of the invention,  
6 seats 121 are furnished with attached uniform 124, which are  
7 each common to uniform 20 and include substantially the same  
8 elements and are each installed to a seat in the same manner  
9 as uniform 20. Uniforms 124 represent baseball uniform  
10 having adornment, which includes style and attached indicia,  
11 that identify the members of the baseball team as  
12 represented by adornment or indicia 122, and include uniform  
13 tops 125 fitted over the seat back portions of seats 121 and  
14 uniform bottoms 126 fitted over the seat portions of seats  
15 121. Although stadium 120 is representative of a baseball  
16 stadium and uniforms 124 baseball uniforms, stadium 120 be  
17 representative of a football stadium, a basketball stadium,  
18 a hockey stadium, etc., and uniforms 124 representative of  
19 those worn by the members of a football team, a basketball  
20 team, a hockey team, etc.

21  
22 FIG. 10 is instructive of the combination of stadium  
23 120 for team sports events with seats 121 for spectators and  
24 team indicia 122 of a team adorning stadium 120, with each  
25 of seats 121 having an attached uniform including top 125

1 fitted over the seat back portion and bottom 126 fitted over  
2 the seat portion, with top 125 and bottom 126 together  
3 supporting adornment/indicia that identify members of the  
4 team commensurate with indicia 122. This embodiment of the  
5 invention is concerned not only with a stadium decorated in  
6 this manner, but also a method that involves providing  
7 uniforms each including a uniform top that is sized and  
8 shaped to be capable of being fitted over the seat back  
9 portion of one of the seats of the stadium and a uniform  
10 bottom that is capable of being fitted over the seat portion  
11 of one of the seats, with the uniform top and the uniform  
12 bottom of each uniform together supporting uniform  
13 adornment/indicia that identify members of the team  
14 commensurate with team adornment/indicia decorating the  
15 stadium. The method next involves fitting the uniform tops  
16 and the uniform bottoms of the uniforms over the seat back  
17 portions and seat portions of the seats. Decorating a  
18 stadium in this fashion is interesting and fun for  
19 spectators and provides an enhanced stadium decoration. Any  
20 number of the seats of a stadium can be furnished with  
21 attached uniforms in accordance with the present embodiment,  
22 whether all of them or selected ones of them.

23

24 Turning now to FIG. 11, depicted is another embodiment  
25 of the invention including a uniform 130 having a uniform

1 top 131 fitted over a seat back portion 132 of a seat 133  
2 and a uniform bottom 134 fitted over a seat portion 135 of  
3 seat 133. Top 131 and bottom 134 together support  
4 camouflage indicia 136 and the embodiment depicted in FIG.  
5 11 is illustrative of this and of the overall design of  
6 uniform 130. FIG. 12 is exemplary of a side elevation of  
7 the embodiment depicted in FIG. 11, with the opposite side  
8 elevation being a mirror image. In structure, uniform 130  
9 is similar to that of uniform 20 previously discussed.  
10 Therefore, further details of the structure of uniform 130  
11 will not be discussed.

12

13 With regard to FIG. 13, depicted is another embodiment  
14 of the invention including a uniform 140 having a uniform  
15 top 141 fitted over a seat back portion 142 of a seat 143  
16 and a uniform bottom 144 fitted over a seat portion 145 of  
17 seat 143. Top 141 and bottom 144 together support  
18 camouflage indicia 146 and the embodiment depicted in FIG.  
19 13 is illustrative of this and of the overall design of  
20 uniform 140. In FIG. 13, seat 143 is a bench and uniform  
21 140 is elongated and adapted and sized to fit thereon in a  
22 manner described previously in connection with uniform 20.  
23 In structure, uniform 140 is similar to that of uniform 20  
24 previously discussed. Therefore, further details of the  
25 structure of uniform 140 will not be discussed.

1       The invention is described above with reference to  
2 preferred embodiments. However, those skilled in the art  
3 will recognize that changes and modifications may be made to  
4 the described embodiments without departing from the nature  
5 and scope of the invention. Accordingly, any such changes  
6 and modifications to one or more of the embodiments herein  
7 chosen for purposes of illustration are intended to be  
8 included within the scope of the invention as assessed only  
9 by a fair interpretation of the ensuing claims.

10

11       Having fully described the invention in such clear and  
12 concise terms as to enable those skilled in the art to  
13 understand and practice the same, the invention claimed is: